Log-periodic antenna 800 MHz to 6 GHz

Main Features

- 800 MHz to 6 GHz frequency range
- Excellent antenna factor
- Tripod adapter for easy vertical-horizontal polarization change
- Individual calibration
- Robust, rustproof aluminium construction
- Lightweight

LP-03 is a log-periodic antenna designed for radiated emissions and immunity testing that can be used in conjunction with any receiver or spectrum analyzer.

Its ideal companion is the EMI Receiver Unit 9060, which can be easily mounted on the antenna mast.*

*The direct connection between antenna and PMM receiver eliminates additional sources of uncertainties due to coaxial cable attenuation and scattering. For further information please consult our brochure "Fully CISPR-Compliant Digital EMC/EMI receivers 10 Hz to 18 GHz".




LP-03

Log-periodic antenna 800 MHz to 6 GHz

SPECIFICATIONS

Frequency range	800 MHz to 6 GHz
Impedance	50 Ω nominal
Gain	6 dBi typical
Antenna factor	23 to 40 dB/m typical
VSWR	< 1,7:1 typical
Construction	Aluminium
Max input power	75 W
Connector	N male (LP-03)
Dimensions (L x H x W)	325 x 81 x 187 mm
Weight	250 g
Colour	RAL 7035



LP-03 Log-periodic Antenna N-male, with individual calibration report LP-03/TC Log-periodic Antenna N-male, with typical calibration report Includes: user's manual, soft carrying case, mounting support, calibration report, N(f)-N(f) adapter

Related products and services

Receivers

Antennas

7010/01: EMI Receiver 9 kHz to 1 GHz


- 7010/03: EMI Receiver 9 kHz to 3 GHz ER8000/00 EMI Receiver 9 kHz to 30 MHz
- ER8000/01 EMI Receiver 9 kHz to 3 GHz
- ER9000/00 EMI Receiver 10 Hz to 30 MHz
- ER9000/01 EMI Receiver 10 Hz to 3 GHz
- 9010F: EMI Receiver 10 Hz to 30 MHz
- 9010/03P: EMI Receiver 10 Hz to 300 MHz
- 9010/30P: EMI Receiver 10 Hz to 3 GHz
- 9010/60P: EMI Receiver 10 Hz to 6 GHz
- 9030: EMI Receiver 30 MHz to 3 GHz
- 9060: EMI Receiver 30 MHz to 6 GHz FR4003: Field Receiver 9 KHz to 30 MHz
- DR-01: Double-ridged Horn Antenna 6 to 18 GHz LP-02: Log Periodic Antenna 200 MHz to 3 GHz

BC-01: Biconical Antenna 30 to 200 MHz

- VDH-01: Van der Hoofden Test Head 20 kHz to 10 MHz
- Antenna Set AS-02 (BC01+LP02+TR01)
- Antenna Set AS-03 (BC01+LP02+LP03+TR01)
- Antenna Set AS-04 (BC01+LP04+TR01)
- Antenna Set AS-05 (BC01+LP04+DR01+TR01)
- Antenna Set AS-06 (BC01+LP-02+LP03+DR01+TR01)
- Antenna Set AS-07 (BL01+TR01)
- Antenna Set AS-08 (BL01+DR01+TR01)
- RA-01: Rod Antenna 9 kHz to 30 MHz
- RA-01-HV: Rod Antenna 150 kHz to 30 MHz
- RA-01-MIL: Rod Antenna 9 kHz to 30 MHz

LP-03 and tripod

कान



TR-01 set includes:

TR01 60-180 cm wooden column extendable tripod, antenna mounting adapter to change polarization, soft carrying case, 5 meter / 6 GHz / N(m)-N(m) RF cable, Antenna Mounting kit AMK-01

Calibration services

- Ansi 63,5 Antenna Factor
- SAE ARP 958-D
- Free-Space Antenna Factor

LP-04: Log Periodic Antenna 200 MHz to 6 GHz TR-01: Antenna Tripod

BL-01: Biconical Log Periodic Antenna 30 MHz to 6 GHz