

Ag

Cu

Ni

Sn

Shieldex® RF Enclosure Table Top

RF - X TBZN3

Series	T-Series
Inner size of the enclosure	610 x 1220 x 610 mm (LxWxH)
Outer size of the frame	752 x 1362 x 732 mm (LxWxH)
Size of the door	870 x 490 mm (WxH)
Material Construction	
Triple Layer	Shieldex® Nora Dell RS Shieldex® Zell RS Shieldex® Berlin RS
Clean Room	Clean Room compatible to A300 (Class 1000)
Shielding Effectiveness	Average 88 dB in a frequency range of 0.03 - 16 GHz
Included	Cable Sleeve, Door, Flooring, Aluminum Frame, Repair Kit, Installation Manual
Optional	I/O Panel
Storage and Handling	According to our care and handling instructions
Compliance and Certification	DIN EN ISO 9001:2015, REACH, RoHS



Electrometric B.V.
Frankrijklaan 7
2391 PX Hazerswoude-Dorp
The Netherlands
T +31 (0)172 423 000
F +31 (0)172 423 009
info@electrometric.com
www.electrometric.com



I/O Panel (passive or anti-interference)

- Power Supply adapters
- Audio / Video adapters
- RF connectors adapters
- Data adapters
- Optical adapters

